


Payment terminals · Self-service and EV charging

WizarPOS Q3V

MDB Master and Slave with a 24 V supply: built for DC chargers, parking meters and vending.

Product code: SPC-PT-Q3V-01



The Q3V is an unattended payment terminal with MDB Master and Slave, pulse and RS232 interfaces, so it can either drive a machine or work alongside its controller. It is a strong fit for DC chargers, parking meters, vending machines and kiosks. The outdoor version has an IP65, IK10 enclosure; the indoor version adds a magnetic stripe reader. An expansion module adds Ethernet and USB-A.

Where it fits

DC chargers · Parking and barriers · Vending

Pre-authorisation

Pre-authorisation and incremental authorisation (as specified by the manufacturer): hold an amount up front and settle what was actually used. Availability depends on the payment application and the acquirer.

Card acceptance

Accepts Visa and Mastercard cards (contactless and chip; magstripe on the indoor version) and mobile wallets – subject to the acquirer.

Key features

MDB Master and Slave

Plus pulse and RS232 for every type of machine.

Two versions

Outdoor with IP65 and IK10, or indoor with a magnetic stripe reader.

Power

24 V DC or from the MDB bus.

Expansion module

Ethernet and USB-A (optional, uses the USB-C port).

4" display

480 × 800 pixels with 1D and 2D code scanning.

Pre-authorisation

Hold an amount before the service and settle afterwards (per manufacturer).

Manufacturer data (WizarPOS) as of October 2026. Certifications are as declared by the manufacturer and apply to specific models and hardware revisions; certificate numbers are available on request. Specifications are subject to change.

Technical specification

PLATFORM

Operating system	Secure Android 14
Processor	Qualcomm Quad-Core 2.0 GHz
Memory	2 GB RAM + 32 GB Flash
Display	4" colour multi-touch, 480 × 800
Card slots	1 × SIM

PAYMENTS

Contactless (NFC)	ISO 14443 A/B, MIFARE, Sony FeliCa
Chip card reader	ISO 7816
Magnetic stripe reader	ISO 7811, tracks 1/2/3, bidirectional (indoor version)
Camera / scanner	1D and 2D barcode scanning
Certifications (manufacturer's declaration)	PCI PTS, EMV L1 and L2, EMV Contactless L1, PayPass, payWave, ExpressPay, D-PAS, Mastercard TQM, SRED, CE, FCC, RoHS

CONNECTIVITY AND PORTS

Connectivity	2G/3G/4G LTE, Wi-Fi, Bluetooth, eSIM (optional)
Ports	MDB Master + MDB Slave / pulse + MDB Slave / RS232; USB-C (OTG)
Expansion module	Ethernet, USB-A (optional, uses the USB-C port)
Positioning	GPS, GLONASS, BeiDou

POWER AND BUILD

Power	24 V DC or MDB bus power
Enclosure	IP65, IK10 (outdoor version)
Operating temperature	-20 to +70 °C
Dimensions (L × W × H)	157 × 102 × 38 mm
Weight	400 g
Mounting	NAMA mounting plate (optional)

In the box

- Q3V terminal in the selected version

Accessories and services

- Terminal activation with remote key injection (RKI)
- Payment application licence and TMS (monthly subscription)
- Integration with the SPACE platform (access control, hotel, EV charging)

Payments

Transactions are settled by the acquirer chosen by the merchant. We help you select and onboard one.

Deployment

Activation, remote key injection and terminal management (TMS) are available from Space BMS.

Contact

Space BMS sp. z o.o., ul. Zbożowa 3/6, 30-002 Kraków, Poland · +48 533 909 533 · www.spacebms.com



Full online catalogue
portal.spacebms.com/kata

Manufacturer data (WizarPOS) as of October 2026. Certifications are as declared by the manufacturer and apply to specific models and hardware revisions; certificate numbers are available on request. Specifications are subject to change.